

	ILCT	DATA	
NO	ノニしょ	DAIA	

TOPOGRAPHY:

TREE REMOVAL:

MAX BUILDING HEIGHT:

Collins Hermle Family Trust 155 San Rafael Way San Francisco, CA 94127 PROPERTY OWNER: DYAR ARCHITECTURE P.O. BOX 4709 CARMEL, CA. 93921 CONTROL FIRM DYAR ARCHITECT/ APPLICANT: PH: 831-915-5602 Mission Street 4 NE OF FIRST AVE. CARMEL-BY-THE-SEA, CA. 93923 PROJECT ADDRESS: APN: 010-112-012 ZONING: 2022 CBC, CRC, CPC, CEC, CMC, CFC, CALIFORNIA ENERGY CODE & CALIFORNIA GREEN BUILDING CODE PROJECT CODE COMPLIANCE: OCCUPANCY GROUP: VB CONSTRUCTION TYPE:

SLOPING TO SOUTH

2-STORY PLATE: 18 FT.

ROOF: 24 FT.

NONE

Floor Area		ALLOWED	EXISTING	PROPOSED
LOT AREA =			4,000 sq. ft.	4,150 sq. ft.
ALLOWABLE BASE FLOOR AREA		1,856 SF	1,321 SF	1,855 SF
4,150 sf x 0.45 - ((150) x .02)				Main 1,188 SF
1,000				Upper 424 SF Garage 243 SF
Site Coverage		ALLOWED	EXISTING	PROPOSED
IMPERMEABLE:		7.2201125		
CONCRETE DRIVEWAY			192 SF	
CONCRETE ENTRY LANDING/ DECK STAIR LANDING/ RETAINING WALLS/ SITE WALLS			78 SF	110 SF
DECOMPOSED GRANITE PATH				127 SF
	TOTAL		270 SF	237 SF
PERMEABLE and SEMI PERMEABLE:				
SIDE YARD PAVERS			5 SF	
GRAVEL PATH			293 SF	
SPACED-BOARD DECKS			435 SF	45 SF
DRIVEWAY PAVERS				115 SF
PAVER ENTRY WALKWAY				170 SF
	TOTAL		733 SF	330 SF
PERCENTAGE PERMEABLE:		>50%	73%	58%
TOTAL SITE COVERAGE		574 SF*	1,003 SF	567 SF
* (1,856 sf x 0.22) + 166 sf Bonus				
Building Heights		ALLOWED	EXISTING	PROPOSED
RIDGE HEIGHTS (1st / 2nd)		18' / 24'	14'-2 3/8" / 0'	16'-6" / 23'-2'
PLATE HEIGHTS (1st / 2nd)		12' / 18'	11'-7" / 0'	11'-7" / 17'-10
Building Setbacks		ALLOWED	EXISTING	PROPOSED
FRONT		15'	32'-11 1/2"	18'-5"
COMPOSITE		10'-4 1/2" (25%)	8'-11 1/2"	11'-8 1/2"
SIDE YARD		3'	2'-10"	3'-9"
SIDE YARD		3'	6'-1 1/2"	7'-11 1/2"
REAR		15'/ ** 3'	14'- 8"	15'-7" / 5'-6"
		.5, 5		.5 . ,5 0

**Rear setback is 3' for portions of structures less than 15' in height

PROJECT DESCRIPTION

Demolition of Existing 1,064 sq. ft. Single-Family Residence, 257 sq. ft. Carport, and Existing Decks.

Project includes a Lot-Line Adjustment of the Existing 40' x 100' (4,000 sq. ft.) Lot. The South Property Line is Shifted to the South by 18" to create the Proposed 41.5' x 100' (4,150 sq. ft.) Lot.

Construction of a New Two-Story, 1,855 sq. ft., Single-Family Residence with 243 sq. ft. attached garage and Includes:

- New Driveway to Replace Existing
 New Stone Garden Walls
 New Stone Paver Entry Walk
 New Stone Outdoor Gas Fireplace
 New 145 sq. ft. Upper Level Deck
 New Wood Fencing
- New Landscaping

SHEET INDEX

Architectural A1 - Cover Sheet and Project Data

- A2 Project Renderings
- Topographic Site Survey
- A3 Preliminary Site Assessment Report
- A4 Combined Main Floor Site Plan
- A5 Combined Upper Floor Site Plan
- A6 Existing and Demolition Plan
- A7 Site and Roof Plan A8 - Main Floor Plan
- A9 Upper Floor Plan A10 - Elevations
- A11 Elevations A12 - Elevations
- A13 Elevations
- A14 Street Elevations
- A15 Materials Sheet A16 - Window and Door Schedules


Civil Engineering

- C1 Conceptual Grading, Drainage, Utility Plan & Sections C2 - Erosion & Sediment Control Plan
- C3 Construction Management Plan

Landscape Architectural

- L0.00 Hapuna Cover Sheet
- L1.00 Overall Site Plan L1.01 - Hapuna Site Plan
- L2.00 Hapuna Planting Plan L2.01 - Hapuna Planting Legend and Notes
- L3.00 Hapuna Lighting Plan

VICINITY MAP



DYAR ARCHITECTURE P.O. BOX 4709 CARMEL, CALIFORNIA 93921 v: 831.915.5602 f: 831.309.9999 Email:

Tract 2 Design Study July 1, 2024 Tract 2 Design Study Resubmittal September 4, 2024

Cover Sheet Project Data



Sheet No. Hapuna



Rendering of Hapuna Residence from Mission Street / Southwest



Rendering of Hapuna Residence from Mission Street / Northwest



© 2024
The Architect's Drawings,
Specifications Or Other Documents
Shall Not Be Used By The Owner
Or Other On Another Project
Except By Agreement In Writing
And With Appropriate
Compensation To The Architect.

<u>Owner:</u> Collins Hermle Family Trust 155 San Rafael Way San Francisco, CA 94127

Residences
Mission Street 4 NE of First Avenucarmel by the Sea, CA 93923
APN: 010-112-012


Job No


Date:
Tract 2 Design Study
July 1, 2024
Track 2 Design
Resubmittal
September 4, 2024

Renderings



A2 Hapuna





BENCHMARK:

ELEVATIONS FOR THIS SURVEY ARE BASED ON AN ASSUMED DATUM. AN ELEVATION OF 50.0 HAS BEEN ASSIGNED TO A MAG NAIL & DISC SET IN THE PAVEMENT NEAR THE WESTERLY BOUNDARY LINE OF LOT 8, BLOCK 8 PER VOLUME 1, C&T PAGE 46 ½ (APN 010-112-013-000) AS SHOWN HEREON.

NOTE

1. BOUNDARY LOCATIONS SHOWN HEREON WERE DETERMINED WITH THE BENEFIT OF A FIELD SURVEY SUPPLEMENTED BY RECORD DATA. ALL BOUNDARY DATA SHOWN HEREON ARE FROM THE RECORDS.

- 2. ENTITLEMENTS OR ENCUMBRANCES AFFECTING THIS PROPERTY MAY NOT NECESSARILY BE SHOWN.
- 3. DISTANCES SHOWN ARE EXPRESSED IN FEET AND DECIMALS THEREOF.
- 4. CONTOUR INTERVAL = ONE FOOT.
- 5. TREE TYPES (IF ANY) ARE INDICATED WHERE KNOWN. DIAMETERS OF TREES ARE SHOWN IN INCHES AND ARE APPROXIMATE ONLY, TO BE VERIFIED BY AN APPROVED ARBORIST PROVIDED BY OTHERS, PER AGREEMENT WITH THE SURVEYOR. TREES SMALLER THAN 6" IN DIAMETER MAY NOT BE NECESSARILY SHOWN. DIRECTION OF GROWTH AND DRIP LINE SHAPE TO BE VERIFIED BY OTHERS.
- 6. POSITION AND DIMENSIONS (IF ANY) OF BUILDINGS AND OTHER STRUCTURES ARE SHOWN HEREON APPROXIMATE ONLY DUE TO MEASUREMENT LIMITATIONS, IRREGULAR SHAPE OF BRICK FACING, POP-OUTS, BULL NOSE CORNERS, ETC. SQUARE FOOTAGE OF BUILDINGS (IF ANY) IS SHOWN APPROXIMATE ONLY, AND SUBJECT TO REVISION AT ANY TIME.
- 7. NOT ALL UTILITY BOXES AND/OR UTILITY STRUCTURES ARE SHOWN INCLUDING BUT NOT LIMITED TO HOSE BIBS AND IRRIGATION VALVES.
 ONLY THE VISIBLE UTILITY BOXES AND/OR UTILITY STRUCTURES THAT WERE CONSIDERED TO CONVEY THE GENERAL UTILITY CONDITIONS ARE SHOWN.
- 8. THIS MAP CORRECTLY REPRESENTS A SURVEY PREPARED BY ME AND/OR UNDER MY DIRECTION, FROM FIELD DATA COLLECTED IN MARCH OF 2023.

TOPOGRAPHIC SITE SURVEY

)F

LOT 6 IN BLOCK 8
PER VOLUME 1, C&T PAGE 46 ½

APN 010-112-012

Records of Monterey County

PREPARED FOR

Craig J. Collins

LUCIDO SURVEYORS

Boundary and Construction Surveys · Topographic and Planimetric Mapping ALTA Surveys and GIS Database Management · Land Planning and Consulting





info@lucidosurveyors.com (831) 620-5032

SCALE: 1"=10' PROJECT No. 3181 APRIL 2022

CITY OF CARMEL COUNTY OF MONTEREY STATE OF CALIFORNIA

Preliminary Site Assessment Survey Mark-Up from City Forester

PRELIMINARY SITE ASSESSMENT REPORT

Date of Site Visit: March 15, 2024 Planner: Marnie R. Waffle Forester: Justin Ono Block/Lot: 8/6 010-112-012 Collins Hermle Family Trust

Street Location: Mission Street 4 NE of 1st Avenue

Purpose: The information contained in this Preliminary Site Assessment is meant to provide input to the applicant on potential project issues prior to project submittal.

Location:

Zoning District	R-1 Single Family Residential
Coastal Commission Appeal Jurisdiction Overlay	No
Archaeological Significance Overlay	Yes
Park Overlay	No
Beach and Riparian Overlay	No
Environmentally Sensitive Habitat Area	No
Very High Fire Hazard Severity Zone	Yes

Street and Neighborhood Character:

- Style and materials of the existing residence:
- Style and materials of the neighboring residences: The Residential Design Guidelines encourage diversity of architectural styles while maintaining compatibility with the character of the neighborhood. A new building should be different in style from buildings on nearby and abutting properties.
- Right-of-way characteristics: The Residential Design Guidelines encourage maintaining and enhancing the informal, vegetated, open space character of the right-of-way. Parking areas in the right-of-way shall be informal, unpaved, and reinforce the forest image. Planting in the right-of-way should be predominately green foliage plants. Native trees, ground covers, and low shrubs are preferred. Gravel is not permitted in the right-of-way.

Site Conditions & Development Standards:

PSA 24021 (Hermle/Collins)

wood or stone and the creative use of landscaping can also help to avoid excess mass by introducing texture, variety and screening."

- <u>Views</u>: The Residential Design Guidelines encourage maintaining view opportunities to natural features that lie outside the property. The Carmel Municipal Code states, "Designs should respect views enjoyed by neighboring parcels. This objective is intended to balance the private rights to views from all parcels that will be affected by a proposed building or addition. No single parcel should enjoy a greater right than other parcels except the natural advantages of each site's topography. Buildings which substantially eliminate an existing significant view enjoyed on another parcel should be avoided."
- <u>Neighborhood Input</u>: Staff strongly recommends reaching out to the adjacent property owners prior to any public hearings to explain the proposed project and address any concerns. Most project delays occur when applicants have not reached out to neighbors

Forest/Trees: Refer to the annotated tree survey and Significant Tree Evaluation Worksheet prepared by the City Forester.

Historic Status: The property was reviewed for historical significance and the staff determination is that the property is not eligible for the historic inventory. A determination of ineligibility will be provided under separate cover.

Design Study Application: The next step is to submit a General Planning Application Form for a <u>Track 2 Design Study</u>. Applications can be submitted online at

https://carmel.portal.iworq.net/portalhome/carmel or by emailing your application materials to planning@ci.carmel.ca.us.

Story Pole Policy: Story poles and netting are required in Carmel-By-The-Sea. The City's Story-Pole Policy was adopted by the City Council in 2017. All story-poles, netting, and ribbons must be installed and certified, in accordance with the Story-Pole Policy, a minimum of 10 calendar days prior to a public hearing. Failure to comply with the Policy could result in the project being continued to a later hearing date.

Additional Resources: For more information on the Design Review Process, Residential Design Guidelines, Carmel Municipal Code, Green Building Ordinance and Title 7A of the Building Code, please visit our website at:

https://ci.carmel.ca.us/community-planning-and-building

PSA 24021 (Hermle/Collins) Page 2 of 6

 <u>Building Site Area</u>: The lot is a standard 4,000-square-foot lot (40'x100'). A base floor area of 1,800 square feet is permitted. A minimum of 200 square feet of the base floor area, and 2,200 cubic feet of exterior volume, shall be reserved for required parking whether provided by a garage, carport, or parking pad.

Floor Area is defined as, "...the total gross square footage included within the surrounding exterior walls of all floors contained within all enclosed buildings on a building site whether finished or unfinished. In above-ground spaces, floor area is measured at the <u>exterior</u> of the enclosing walls. In basement spaces, floor area is measured at the <u>interior</u> of the enclosing walls. Floor area shall include, but shall not be limited to, all floors of all enclosed spaces within all buildings, basements, mezzanines, guesthouses, studios, garages, and carports. All attic, basement, and storage shed spaces with five or more feet of clearance between the floor or walking surface and the ceiling or roof surface shall be counted as floor area. All required parking shall be counted as floor area, whether supplied by garage, carport or other means."

• <u>Setbacks</u>: The minimum front and rear setbacks are 15 feet. The composite side yard setback is 25% of the lot width with a 3-foot minimum on one side.

			Side Setbacks						
Lot Type	Front Setback (in	Rear Setback* (in	Composite" (both		Setbacks (in feet)				
	-		sides)	Interior Side	Street Side				
Interior Site	15	15	25% of site width	3	N/A				
Corner Site	15	15	25% of site width	3	5				
Resubdivided Corner Side	10	15	25% of site width	3	9				
Double-Frontage Site	15	N/A	25% of site width	3	5 (if applicable)				

- * The rear setback is three feet for those portions of structures less than 15 feet in height.
- ** See CMC 17.10.030(A)(1) and 17.05.030. Rules of Measurement.
- <u>Building Height</u>: The height of buildings shall be measured as the plumb vertical distance from existing or finished grade (whichever is more restrictive) to the highest point on the

PSA 24021 (Hermle/Collins)

Table	17.10-C: Maximum H	eight Standards	
	R-1 District	R-1-BR District	R-1-PO District
Number of Stories Allowed	2	2	1*
Roof Height of First Story (in feet)	18	18	18
Plate Height of First Story (in feet)	12	12	12
Roof Height of Second Story (in feet)	24	18	24*
Plate Height of Second Story (in feet)	18	18	18*

Page 3 of 6

• Exterior Volume: The maximum allowable exterior volume is the total allowed base floor area for the site multiplied by the volume factors in Table 17.10-E (refer to table below). It is recognized that existing homes built prior to 2003 may not have been designed to comply with volume standards. For these homes, the Code allows the exterior volume to be calculated for additions only.

Table 17.10-E: Exterior V	folume Factors for R-1 Distr	iet
		ne (Cubic Feet) Per Square Floor Area
	One-Story Elements of the Building	Two-Story Elements of the Building
Located under a pitched or sloping roof greater than 3:12 pitch	12	11
Located under a flat roofed area of the building 3.12 or less pitch	11	10

- Parking: One parking space per primary dwelling is required on sites 8,000 square feet or less. Required parking shall be provided by a garage, carport or parking pad measuring at least 10 feet by 20 feet having practical ingress and egress for a vehicle. All required parking shall be provided on-site and shall be counted as floor area and exterior volume. On each site, a minimum of 200 square feet of base floor area and 2,200 cubic feet of exterior volume shall be reserved for each required parking space whether provided by means of a garage, carport or parking pad.
- <u>Garage</u>: To encourage variety and diversity in neighborhood design, detached garages and carports may be authorized by the Planning Commission within the front setback and/or side yard setback facing a street. Garages permitted to be located within a setback are limited to a single-car, detached structure not exceeding 12 feet in width, 250 square feet in floor area and 15 feet in height. Detached garages may encroach into an interior side yard setback, rear yard setbacks, or both, if limited to 15 feet in height, the setback encroachment would not impact significant or moderately significant trees, and the garage location/design complies with design guidelines.

PSA 24021 (Hermle/Collins) Page 4 of 6

• Accessory Structures: Up to two accessory structures may be constructed on the property. Accessory structures cannot exceed 400 square feet in floor area (unless an exception applies) and count towards to the total base floor area allowed for the site. Sheds that exceed 5 feet in height also count as floor area.

Studio: A studio is defined as, "An attached or detached residential dwelling unit without kitchen or cooking facilities, designed for accessory uses by occupants of the dwelling to which it is accessory, and not designed or intended for living, sleeping and/or cooking. Studios are permitted to have a bathroom with a sink and toilet. Studios that are attached to the primary dwelling are not required to have interaccessibility with the primary dwelling."

One studio is permitted so long as it does not contain any living, sleeping, bathing or food preparation facilities of any kind. Studios may have a bathroom with a sink and toilet. Studios that are attached to the primary dwelling are not required to have inter-accessibility with the primary dwelling. No additional parking is required for a studio. Studios shall be a maximum size of 400 square feet and shall not exceed the allowed floor area ratio for the lot.

Accessory Dwelling Units (ADUs): One accessory dwelling unit and one junior accessory dwelling unit are permitted pursuant to CA State Law. For more information, please refer to the <u>Accessory Dwelling Unit Handbook</u>.

• <u>Topography and drainage features:</u> The Residential Design Guidelines encourage designs that follow the natural contours of the site and that avoid abrupt changes in grade on the site and between properties. A preliminary grading and drainage plan is required to be submitted with the Design Study application and will be reviewed by the Environmental Compliance Manager. Feedback on potential drainage issues and solutions will be

Following design approval, plans that are submitted for a building permit must include a complete storm water drainage plan. The drainage plan shall include applicable Best Management Practices and all drainage shall be retained on-site through the use of semipermeable paving materials, French drains, seepage pits, etc. Properties located in areas with poor soil drainage will be required to have systems designed by an engineer.

• <u>Site Coverage</u>: Impermeable site coverage is limited to 22% of the base floor area for the site or **396 square feet** for a base floor area of 1,800 square feet. Impermeable materials include, asphalt, concrete, mortared brick and stone, decomposed granite, unspaced decking and balconies at any level, garden walls, solariums, bridges, sheds not counted as floor area, ponds, hot tubs, and swimming pools.

If at least 50 percent of all site coverage on the property is made of permeable or semipermeable materials, an additional amount of site coverage of up to four percent of the

Tree # 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

or has poor soil for the species.

Part Three: Final Assessment

(Explain any 'yes' answer)

other trees are classified as non-significant.

light, air and soils suitable for the species.

Record the total points scored on D - G for each tree.

YES X X X X X X X X X

The tree is crowded or has no room for growth to maturity. The tree has poor access to light, air

The tree has average environmental conditions including room for growth to maturity, access to

The tree has room for growth to maturity with no crowding from other significant trees or

Tree # 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Total 7 8 6 6 7 7 7 7 7

Tree # 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

B. Are there any other factors that would disqualify a tree from a determination of significance?

Conclusion: Does The Tree Qualify As Significant Or Moderately Significant?

If the tree meets the species, size and safety criteria identified in Part One and scores at least one point

under each of the criteria in Part Two, it shall be classified as Significant if it achieves a score of **6 or more**

points or shall be classified as Moderately Significant if it achieves a score of 4 or 5 points. Tree species not

listed in Part One-B that meet other screening criteria in Part One may be classified by the City Forester as

Significant if they score at least 7 points, or as Moderately Significant if they score at least 4 points. All

A. Did all assessment categories in Part Two achieve a minimum score of 1-point?

2 points: existing buildings nearby. The tree also has excellent access to light, air and excellent soils for

Page 5 of 6 PSA 24021 (Hermle/Collins)

site area, **160 square feet**, may be utilized. Permeable and semi-permeable materials include, gravel, spaced decking and exterior stairs, sand-set bricks or pavers, garden walkways of small paving stones, and arbors.

• Fences: Fences within the front setback are limited to 4 feet in height. This limit cannot be increased through a Design Study. Side and/or rear yard fences are permitted a height of 6 feet and may be taller with approval by the Planning Commission. The heights should be clearly noted on the project plans.

	Table 17.10-0:	Maximum Track	One Fence and Wall Heights	
			Setback Location	V. I.
Design Element	Front Setback	Side Setback	Side Setback Facing Street	Rear Setback
Fence	4 feet*	6 feet	4 feet*	6 feet
Garden Wall	3 feet*	6 feet	3 feet*	6 feet
Retaining Wall	3 feet**	6 feet	3 feet**	6 feet
Pillars and Gates	6 feet	NA	6 feet	NA
Arbor/Trellis	7 feet	7 feet	7 feet	7 feet

- These limits shall not be aftered through Design Review by the Planning Commission.
- " Up to six feet may be allowed for retaining walls that are not visible from the street. See CMC 17.10.000(E)(4).

Potential Neighbor Impacts:

- Privacy: The Residential Design Guidelines encourage preserving reasonable privacy for adjacent properties and locating windows such that they avoid overlooking active indoor and outdoor use areas of adjacent properties. Additionally, the Guidelines recommend screening patios and terraces.
- <u>Solar Access:</u> The Residential Design Guidelines encourage maintaining solar access for adjacent properties. The Carmel Municipal Code states, "Designs should preserve the rights to reasonable solar access on neighboring parcels. Excessively tall buildings, particularly those near a north property line, which would block the free passage of the sun onto neighboring solar collectors or south-facing windows on neighboring sites, should be avoided."
- Mass and Bulk: The Residential Design Guidelines encourage thoughtful design when it comes to bulk and massing. The Carmel Municipal Code states, "Residential designs shall maintain Carmel's enduring principles of modesty and simplicity and preserve the City's tradition of simple homes set amidst a forest landscape. Buildings shall not present excess visual mass or bulk to public view or to adjoining properties. Large box-like buildings and buildings with large, continuous, unrelieved surfaces can appear massive. Designing building and roof planes with just a few, simple forms and keeping floor levels and plate heights close to grade help reduce mass and bulk. The use of natural materials such as

Required Structural Root Zone

Troo # 1 2 2 4 5 6 7 9 9 10 11 12 12 14 15 Feet 6 6 6 6 6 6 8 Tree # 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15

Requirements for tree preservation shall adhere to the following tree protection measures on construction

YES 8 8 8 8 8 8 8 12

Prior to grading, excavation, or construction, the developer shall clearly tag or mark all trees to be

Excavation within 6 feet of a tree trunk is not permitted.

No attachments or wires of any kind, other than those of a protective nature shall be attached to any

Per Municipal Code Chapter 17.48.110 no material may be stored within the dripline of a protected tree to include the drip lines of trees on neighboring parcels.

Tree Protection Zone -- The Tree Protection Zone shall be equal to dripline or 18 inches radially from the tree for every one inch of trunk diameter at 4.5 feet above the soil line, whichever is greater. Minimum of 4 foot high transparent fencing is required unless otherwise approved by the City Forester. Tree protection shall not be resized, modified, removed, or altered in any manner without written approval. The fencing must be maintained upright and taught for the duration of the project. No more than 4 inches of wood mulch shall installed be within the Tree Protection Zone. When the Tree Protection Zone is at or within the drip line, no less than 6 inches of wood mulch shall be installed 18 inches radially from the tree for every one inch of trunk diameter at 4.5 feet above the soil line outside of fencing.

The Structural Root Zone -- Structural Root Zone shall by 6 feet from the trunk or 6 inches radially from the tree for every one inch of trunk diameter at 4.5' above the soil line, whichever is greater. Any excavation or changes to the grade shall be approved by the City Forester prior to work. Excavation within the Structural Root Zone shall be performed with pneumatic excavator, hydrovac at low pressure, or other method that does not sever roots.

If roots greater than 2 inches in diameter or larger are encountered within the approved Structural Root Zone the City Forester shall be contacted for approval to make any root cuts or alterations to structures to prevent roots from being damaged.

If roots larger than 2 inches in diameter are cut without prior City Forester approval or any significant tree is endangered as a result of construction activity, the building permit will be suspended and all work stopped until an investigation by the City Forester has been completed and mitigation measures have been put in place.

Specifications Or Other Docume Shall Not Be Used By The Own Or Other On Another Project Except By Agreement In Writing And With Appropriate Compensation To The Architect.

DYAR ARCHITECTURE

P.O. BOX 4709 CARMEL, CALIFORNIA 93921 v: 831.915.5602 f: 831.309.9999

Owner: Collins Hermle Family Trus 155 San Rafael Way San Francisco, CA 94127

lapuna lesidence ssion Street 4 NE of First rmel by the Sea, CA 939. N: 010-112-012

Tract 2 Design Study Resubmittal September 4, 2024

Preliminary Site Assessment Report



Significant Tree Evaluation Worksheet

Street Location: Mission St 4 NW 1st Ave Planner: Marnie Waffle City Forester: Justin Ono Property Owner: Hermle-Collins Recommended Tree Density: 3 upper, 1 lower

Part One: Initial Screening:

Complete Part One to determine if further assessment is warranted. Trees must pass all criteria in Part One to be considered significant or moderately significant.

A. Does	the tr	ee pos	se an	above-	-norm	al pote	ential i	risk to	life ar	nd pro	perty?				
Tree #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
YES															
NO	Х	X	X	X	Х	Х	Х	X							

Any tree with structural impairment likely to cause failure should be marked as unsafe and removed. Use page five of this worksheet to document the safety risk. Trees that have limited and specific defects that can be remedied with selective pruning or other mitigation should be marked as safe and specific recommendations should be given to the owner for tree care. Such trees may still be assessed for significance.

Tree #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Species	CO	MP	CO	CO	CO	Pitt	Pitt	MP							
YES	Х	Х	Х	Х	Х			Х							
NO	X	X	Х	Х	Х	×	v	Х							

MP-Monterey pine MC- Monterey cypress BP-Bishop pine CR -coast redwood CO- coast live oak CI -- Catalina ironwood CS -- California sycamore BL -- big leaf maple Pitt -- Pittosporum OT -- other

(Note: Other species on the recommended tree list may be determined to be Significant Trees only if they are exceptional examples of the species. Such trees also must exhibit excellent health, form, vigor, and substantial size to rate an overall score of at least 7 points in Part Two of the

C. <u>Doe</u>	C. <u>Does the tree meet the minimum size criteria for significance?</u>														
Tree #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
YES	Х	Х	Х	Χ	Х	Х	Χ	Χ							
NO															

Monterey pine, Monterey cypress, Bishop pine, Coast redwood: 6" DBH Coast live oak – single trunk tree: 6" DBH Coast live oak – multi-trunk tree measured per industry standard: 6" DBH California sycamore, Big leaf maple, Catalina ironwood, other: 10" DBH dbh = diameter at breast height or 4.5 feet above the adjacent ground surface Part Two: Assessment For Tree Significance For each of the criteria below assign points as shown to assess the tree. If any criteria score is zero the assessment may stop as the tree cannot qualify as significant or moderately significant.

Tree # 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 score 2 2 1 1 2 2 2 2 2 **O points:** The tree is heavily infested with pests or has advanced signs of disease that indicates the tree is declining and has very limited life expectancy. The tree shows some pests or disease that impair its condition, but which does not immediately threaten the health of the tree. The

D. What is the health and condition of the tree?

2 points:													
				_									
	- 1	1						1					
3 points:	ine tree s	snows ex	cellent n	ieaith, is t	ree or pes	its and di	sease and	is in very	strong c	onaition.			

score 2 2 2 2 2 2 2 2 2 ... Prior pruning, disease or growth habit have left the tree deformed or unsound to an extent that it cannot 0 points: recover or will never be a visual asset to the neighborhood or will likely deteriorate into a structural hazard.

The tree has poor form or structure but (a) can recover with proper maintenance or (b) it provides visual 1 point: interest in its current form, and does not have structural defects that are likely to develop into a safety hazard. The tree has average form and structure for the species but does not exhibit all the qualities of excellent

The tree exhibits excellent form and structure. For all species there will be a good distribution of foliage on multiple branches with no defects. For conifers, the tree will have a single straight leader with balanced branching and with good taper. Oaks will exhibit a well-developed canopy with no suppressed branches.

	Oaks n	nay be s	ingle-t	runked	or mult	i-trunke	ed and v	will have	e a bala	nced di	stributi	on of fo	liage or	າ each	
F. Wh	at is tl	he age	e and	vigor	of the	tree	2								
Tree #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	1
														4	

2 points: The tree is young to middle age and shows normal vigor.

3 points: The tree is young to middle age and shows exceptional vigor.


score 2 2 2 2 2 2 2 1


The tree is over-mature or shows signs of poor or declining vigor such as die-back of major limbs or of the crown, small leaves/needles and/or minimal new growth. The tree is mature but retains normal vigor and is likely to continue as a forest asset for a substantial period **1 point**: into the future.











Hapuna Residence
Mission Street 4 NE of First Avenue
Carmel by the Sea, CA 93923
APN: 010-112-012

Track 2 Design Study July 1, 2024 Track 2 Design Resubmittal September 4,2024

Mission Sisters Properties Main Level Site Plan and Street Elevation

1/8" = 1'-0"



A4 Hapuna

Overall Main Floor Site Plan


Scale: 1/8" = 1'-0"


ACCENT BOULDER


DECOMPOSED GRANITE PATH SPACED-BOARD WOOD DECK

MULCH PATH CARMEL STONE GARDEN WALL

NEW FENCE NEW PLANTING OR LANDSCAPE AREA CORTEN STEEL RETAINING WALL _ -100 EXISTING CONTOUR WOOD PAVERS PROPOSED CONTOUR
















Owner: Collins Hermle Family Trust 155 San Rafael Way San Francisco, CA 94127

Hapuna Residence
Mission Street 4 NE of First Avenue
Carmel by the Sea, CA 93923
APN: 010-112-012

Track 2 Design Study July 1, 2024 Track 2 Design Resubmittal September 4, 2024

Mission Sisters
Properties
Upper Level
Site Plan
and Street
Elevation

1/8" = 1'-0"



A5 Hapuna


Overall Upper Floor Site Plan


Scale: 1/8" = 1'-0"


LEGEND

STONE PAVER DECK

GREEN ROOF -100 EXISTING CONTOUR







© 2024
The Architect's Drawings,
Specifications Or Other Documents
Shall Not Be Used By The Owner
Or Other On Another Project
Except By Agreement In Writing
And With Appropriate
Compensation To The Architect.

Owner: Collins Hermle Family Trust 155 San Rafael Way San Francisco, CA 94127

Hapuna Residence
Mission Street 4 NE of First Avenue
Carmel by the Sea, CA 93923
APN: 010-112-012


Track 2 Design Study July 1, 2024 Track 2 Design Study Resubmittal September 4, 2024


Existing and **Demolition** Site Plan

1/4" = 1'-0"



A6 Hapuna





DYAR ARCHITECTURE P.O. BOX 4709 CARMEL, CALIFORNIA 93921 v: 831.915.5602 f: 831.309.9999 Email: info@dyararchitecture.com

Hapuna Residence
Mission Street 4 NE of First Avenue
Carmel by the Sea, CA 93923
APN: 010-112-012


Track 2 Design Study July 1, 2024 Track 2 Design Study Resubmittal September 4, 2024


Main Floor Plan

1/4" = 1'-0"




Sheet No. **A8** Hapuna





Existing West Elevation


Scale: 1/4" = 1'-0"



Proposed Hapuna West Elevation

Scale: 1/4" = 1'-0"

DYAR
ARCHITECTURE
P.O. BOX 4709
CARMEL, CALIFORNIA 93921
v: 831.915.5602
f: 831.309.9999
Email:
info@dyararchitecture.com








ob No.


Date:
Track 2 Design Study
July 1, 2024
Track 2 Design Study
Resubmittal
September 4, 2024

Hapuna West Elevations


1/4" = 1'-0"



A10
Hapuna




Proposed Hapuna North Elevation Scale: 1/4" = 1'-0"




Proposed Hapuna North Elevation

Scale: 1/4" = 1'-0"










Job No.

Tract 2 Design Study
July 1, 2024

Tract 2 Design Study
Resubmittal
September 4, 2024


Hapuna North Elevations

1/4" = 1'-0"




A11
Hapuna






Existing East Elevation




Proposed Hapuna East Elevation

Scale: 1/4" = 1'-0"








Hapuna Residence
Mission Street 2 NE of First Avenue
Carmel by the Sea, CA 93923
APN: 010-112-012

No.

Date:
Tract 2 Design Study
July 1, 2024
Tract 2 Design Study
Resubmittal
September 4, 2024


Hapuna East Elevations

1/4" = 1'-0"



A12
Hapuna

Proposed Hapuna South Elevation Scale: 1/4" = 1'-0"



Proposed Hapuna South Elevation

Scale: 1/4" = 1'-0"

DYAR
ARCHITECTURE
P.O. BOX 4709
CARMEL, CALIFORNIA 93921
v: 831.915.5602
f: 831.309.9999
Email:
info@dyararchitecture.com

© 2024
The Architect's Drawings,
Specifications Or Other Documents
Shall Not Be Used By The Owner
Or Other On Another Project
Except By Agreement In Writing
And With Appropriate
Compensation To The Architect.

Owner: Collins Hermle Family Trust 155 San Rafael Way San Francisco, CA 94127

Hapuna Residence
Mission Street 2 NE of First Avenue
Carmel by the Sea, CA 93923
APN: 010-112-012


Job No.

Tract 2 Design Study
July 1, 2024

Tract 2 Design Study
Resubmittal
September 4, 2024

Hapuna South Elevations


1/4" = 1'-0"




A13
Hapuna



Proposed Street Elevation








Photographs of Existing Street Elevation



© 2024
The Architect's Drawings,
Specifications Or Other Documents
Shall Not Be Used By The Owner
Or Other On Another Project
Except By Agreement In Writing
And With Appropriate
Compensation To The Architect.



Hapuna Residence
Mission Street 4 NE of First Avenue
Carmel by the Sea, CA 93923
APN: 010-112-012

No.

Date:
Track 2 Design Study
July 1, 2024

Track 2 Design
Resubmittal
September 4, 2024

Hapuna Existing and Proposed Street Elevations



A 14
Hapuna






RECESSED SOFFIT LIGHT 55822, Bega, LED Recessed ceiling down light #4 Brushed aluminum 316 stainless steel finish 4.2 Watt: 299 Lumen

Exterior Recessed Soffit Light





Wood Siding
Stained Natural Wood Siding




Siding WidthSiding Width: 4" Board



Varying Width Standing Seam Metal Roof



Stone Garden Walls



Stone Pavers




Exterior Windows + Doors
Sapele Wood





Spaced-Board Wood Deck

Ipe Wood




Landscape Boulders
Accent and Retaining Boulders













bb No.
































Type 'A' Fixed Window

Type 'B' Casement/ Fixed Window

Type 'C' Fixed/ Casement Window


Type 'D' Awning Window

Type 'E' Fixed/ Awning Window


Type 'F' Casement Window

Type 'G' Fixed Corner Window

Door No.	Location	Room No.	Frame Width	Frame Height	Door Thickness Ty	ype Door Material	Glazing Type	Frame / Jamb Material	Manufacturer Remarks
Main Hou				<u> </u>	<u> </u>				
	Garage	100	8'-0"	7'-0"	1-3/4"	A Stain-Grade Wood		Stain-Grade Wood	Garage Door
	Garage	100	3'-0"	6'-8"		B Stain-Grade Wood		Stain-Grade Wood	Exterior Swing Door with Insulated Tempered Glass
3	Kitchen	101	3'-0"	6'-8"	1-3/4"	C Paint-Grade Wood		Paint-Grade Wood	Interior Swing Door
4	Kitchen	103	3'-0"	8'-0"	1-3/4" I	D Stain-Grade Wood	1" Insulated Glass, Tempered	Stain-Grade Wood	Dutch Door Solid Core Paint Grade with Tempered Insulated Glass
5	Entry	103	3'-3"	7'-10"	1-3/4" I	E Stain-Grade Wood		Stain-Grade Wood	Exterior Swing Door
6	Powder Room	105	2'-6"	6'-8"	1-3/4"	C Paint-Grade Wood		Paint-Grade Wood	Interior Swing Door
7	Storage	107	2'-8"	6'-8"	1-3/4"	C Paint-Grade Wood		Paint-Grade Wood	Interior Swing Door
8	Bedroom 1	109	2'-8"	6'-8"	1-3/4"	C Paint-Grade Wood		Paint-Grade Wood	Interior Swing Door
9	Bathroom	110	2'-6"	6'-8"	1-3/4"	C Paint-Grade Wood		Paint-Grade Wood	Interior Swing Door
10	Bedroom 2	111	2'-8"	6'-8"	1-3/4"	C Paint-Grade Wood		Paint-Grade Wood	Interior Swing Door
11	Bedroom 2	111	8'-0"	7'-4"	1-3/4" I	F Stain-Grade Wood	1" Insulated Glass, Tempered	Stain-Grade Wood	Slider Door
12	Closet	111.1	2'-4"	6'-8"	1-3/4"	G Paint-Grade Wood		Paint-Grade Wood	Pocket Door
13	Primary Suite	201	8'-0"	7'-6"	1-3/4" I	H Paint-Grade Wood	1" Insulated Glass, Tempered	Paint-Grade Wood	Exterior Solid Core Pocket Door with Insulated Tempered Glass
14	Primary Closet	201.1	3'-6"	6'-8"	1-3/4"	J Paint-Grade Wood		Paint-Grade Wood	Interior Double Pocket Door
15	Primary Bathroom	202	2'-6"	6'-8"	1-3/4"	C Paint-Grade Wood		Paint-Grade Wood	Interior Swing Door
16	Primary Bathroom: Water Closet	202.1	2'-6"	6'-8"	1-3/4"	G Paint-Grade Wood		Paint-Grade Wood	Interior Pocket Door




Type 'A' Garage Door




Type 'C' Interior Solid Core

Swing Door





Core Dutch Door with Insulated

Tempered Glass




Exterior Solid Core Swing Door






Exterior Solid Core Double Slider with


Insulated Tempered Glass




Interior Solid Core Pocket Door









Type 'J' Interior Solid Core Double Pocket Door









Hapuna
Residences
Mission Street 4 NE of First Avel
Carmel by the Sea, CA 93923
APN: 010-112-012

Tract 2 Design Study July 1, 2024 Track 2 Design Resubmittal September 4, 2024

Door and Window **Schedules**







PLAN

EROSION & SEDIMENT CONTROL NOTES:

- 1) ALL EROSION CONTROL MEASURES SHALL CONFORM WITH THE CITY OF CARMEL-BY-THE-SEA EROSION CONTROL ORDINANCE.
- 2) EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IN EFFECT FOR ANY CONSTRUCTION DURING THE RAINY SEASON, APPROX. OCTOBER 15 TO APRIL 15. EROSION CONTROL PLAN SHALL BE PREPARED AND SUBMITTED FOR APPROVAL BY SEPT. 15 OF ANY OR EACH CALENDAR YEAR THAT CONSTRUCTION MAY EXTEND BEYOND OCTOBER 15.
- 3) ALL SLOPES SHALL BE PROTECTED WITH STRAW MULCH OR SIMILAR MEASURES TO PROTECT AGAINST EROSION UNTIL SUCH SLOPES ARE PERMANENTLY STABILIZED.
- 4) RUNOFF SHALL BE DETAINED OR FILTERED BY BERMS, VEGETATED FILTER STRIPS, AND/OR CATCH BASINS TO PREVENT THE ESCAPE OF SEDIMENT FROM THE SITE.
- 5) EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IN PLACE AT THE END OF EACH DAY'S
- 6) EROSION CONTROL PLANTINGS AND MULCH SHALL BE CLOSELY MONITORED THROUGHOUT THE WINTER AND ANY RUNOFF PROBLEMS CORRECTED PROMPTLY. SEE LANDSCAPE ARCHITECT'S PLAN FOR PERMANENT PLANTINGS AND TREE SCHEDULES.
- 7) DISTURBED SURFACES NOT INVOLVED IN THE IMMEDIATE GRADING OPERATIONS MUST BE PROTECTED BY MULCHING AND/OR OTHER EFFECTIVE MEANS OF SOIL PROTECTION.
- 8) ALL ROADS AND DRIVEWAYS SHALL HAVE DRAINAGE FACILITIES SUFFICIENT TO PREVENT EROSION ON OR ADJACENT TO THE ROADWAY OR ON THE DOWNHILL PROPERTIES.
- 9) DRAINAGE CONTROL MEASURES SHALL BE MAINTAINED AND IN PLACE AT THE END OF EACH DAY AND CONTINUOUSLY THROUGHOUT THE LIFE OF THE PROJECT DURING WINTER OPERATIONS.
- 10) REVEGETATION SHALL CONSIST OF A MECHANICALLY APPLIED HYDROMULCH SLURRY OR HAND SEEDED WITH A STRAW MULCH COVER. MULCH SHALL BE ANCHORED BY AN APPROVED METHOD SUCH AS PUNCHING, TACKING, OR THE USE OF JUTE NETTING, AS DEEMED NECESSARY FOR THE SITE CONDITIONS TO ALLOW FOR GERMINATION AND ENABLE ADEQUATE GROWTH TO BE
- 11) CHECK DAMS, SILT FENCES, FIBER ROLLS OR OTHER DESIGNS SHALL BE INCORPORATED TO CATCH ANY SEDIMENT UNTIL AFTER THE NEWLY EXPOSED AREAS ARE REVEGETATED SUFFICIENTLY TO CONTROL EROSION. EROSION CONTROL PLANTINGS AND MULCH SHALL BE CLOSELY MONITORED THROUGHOUT THE WINTER AND ANY RUNOFF PROBLEMS SHALL BE CORRECTED PROMPTLY. ALL EROSION AND/OR SLIPPAGE OF THE NEWLY EXPOSED AREAS SHALL BE REPAIRED BY THE PERMITTEE AT THEIR EXPENSE.
- 12) THE GRASS SEED SHALL BE PROPERLY IRRIGATED UNTIL ADEQUATE GROWTH IS ESTABLISHED AND MAINTAINED TO PROTECT THE SITE FROM FUTURE EROSION DAMAGE. ALL NEWLY EXPOSED (DISTURBED) AREAS SHALL BE SEEDED WITH THE FOLLOWING EROSION CONTROL MIX: BROMUS CARINATUS (CALIFORNIA BROME), VULPIA MICROSTACHYS (NUTTALL'S FESCUE), ELYMUS GLAUCUS (BLUE WILD RYE), HORDEUM BRACHYANTHERUM (MEADOW BARLEY), FESTUCA RUNRA'MOLATE BLUE AND A MIXTURE OF LOCALLY NATIVE WILDFLOWERS.
- 13) THE DIRECTOR OF BUILDING INSPECTION (BUILDING OFFICIAL) SHALL STOP OPERATIONS DURING PERIODS OF INCLEMENT WEATHER IF HE OR SHE DETERMINÉS THAT EROSION PROBLEMS ARE NOT BEING CONTROLLED ADEQUATELY.
- 14) GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR EROSION AND SEDIMENT CONTROL BMP INSTALLATION AND MAINTENANCE AND SHALL PROVIDE FULL PARTICULARS TO THE CITY OF CARMEL-BY-THE-SEA PRIOR TO BEG. WORK.

TABLE 1706.6 REQUIRED VERIFICATION AND INSPECTION OF SOILS

VERIFICATION AND INSPECTION TASK	CONTINUOUS DURING TASK LISTED	PERIODICALLY DURING TASK LISTED
 Verify material below shallow foundations are adequate to achieve the design bearing capacity 		X
2. Verify excavations are extended to proper depth and have reached proper material		X
3. Perform classification and testing of compacted fill materials		X
4. Verify use of proper materials, densities and lift sicknesses during placement and compaction of compacted fill.	Х	
5. Prior to placement of compacted fill, observe subgrade and verify that site has been prepared properly.		Х

CONSTRUCTION INSPECTION REQUIREMENTS

- A-PRIOR TO COMMENCEMENT OF ANY LAND DISTURBANCE, THE OWNER/APPLICANT SHALL SCHEDULE AN INSPECTION WITH HCD-ENVIRONMENTAL SERVICES TO ENSURE ALL NECESSARY SEDIMENT CONTROLS ARE IN PLACE AND THE PROJECT IS COMPLIANT WITH MONTEREY COUNTY GRADING AND EROSION CONTROL REGULATIONS.
- B-DURING CONSTRUCTION THE OWNER/APPLICANT SHALL SCHEDULE AN INSPECTION WITH HCD-ENVIRONMENTAL SERVICES TO UPDATE COMPACTION TEST RECORDS, INSPECT DRAINAGE DEVICE INSTALLATION, REVIEW THE MAINTENANCE AND EFFECTIVENESS OF BMP's INSTALLED, AS WELL AS, TO VERIFY THAT POLLUTANTS OF CONCERN ARE NOT DISCHARGED FROM THE SITE.
- C-PRIOR TO FINAL INSPECTION, THE OWNER/APPLICANT SHALL SCHEDULE AN INSPECTION WITH HCD-ENVIRONMENTAL SERVICES TO CONDUCT A FINAL GRADING INSPECTION, COLLECT FINAL GEOTECHNICAL LETTER OF CONFORMANCE, ENSURE THAT ALL DISTURBED AREAS HAVE BEEN STABILIZED AND THAT ALL TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES THAT ARE NO LONGER NEEDED HAVE BEEN REMOVED.

LEGEND:

, , , , , , , ,

TRASH

RECYCLE

FIBER ROLLS: THE CONTRACTOR SHALL MAINTAIN A STOCKPILE OF FIBER ROLLS ONSITE, AS THEY CAN BE USED ALONG ERODIBLE SLOPES, ALONG STOCKPILE PERIMETERS, DOWNSLOPE OF EXPOSED SOIL AREAS, AND TO DELINEATE/PROTECT STAGING AREAS. FIBER ROLLS MUST BE TRENCHED INTO THE SOIL AND STAKED (STAKES SPACED MAX. 4' ON CENTER), SEE DETAIL, INSTALL FIBER ROLLS ALONG LEVEL CONTOURS, AND TURN THE ENDS UPHILL INSPECT WEEKLY AND REMOVE ACCUMULATED SEDIMENT REGULARLY.

DRAIN INLET PROTECTION: PLACE GEOTEXTILE FILTER FABRIC BENEATH INLET GRATE AND SURROUND ENTIRE INLET WITH GRAVEL BAGS (OVERLAP THE BAGS AND PACK THEM TIGHTLY TOGETHER - SEE DETAIL). INSPECT ALL INLET PROTECTION WEEKLY. REMOVE ACCUMULATED

STABILIZED CONSTRUCTION ACCESS: INSTALL STABILIZED CONSTRUCTION ACCESS PRIOR TO COMMENCEMENT OF EARTH MOVING OPERATIONS (SEE DETAIL). INSPECT ENTRANCE DAILY, AND ADD ADDITIONAL STONE AS TOP-DRESSING WHEN REQUIRED. USE FENCING OR BARRICADES TO PREVENT VEHICLE TRAFFIC FROM DRIVING AROUND THE STABILIZED ACCESS.

CONCRETE WASHOUT: WASHOUT MUST BE LOCATED A MINIMUM OF 50 FEET FROM STORM DRAINS, OPEN DITCHES, OR WATER BODIES. DISCONTINUE USE WHEN WASHOUT WASTES REACH 75% OF THE WASHOUT CAPACITY. ALLOW WASHOUT WASTES TO HARDEN, BE BROKEN UP, AND THEN DISPOSED OF PROPERLY.

SANITARY/SEPTIC WASTE MANAGEMENT: PORTABLE TOILETS WILL BE PROVIDED AND MAINTAINÉD ONSITE FOR THE DURATION OF THE PROJECT. ALL PORTABLE TOILETS WILL BE EQUIPPED WITH A SECONDARY CONTAINMENT TRAY, AND SHALL BE LOCATED A MINIMUM OF 50' FROM ALL OPERATIONAL STORM DRAIN INLETS. WEEKLY MAINTENANCE SHALL BE PROVIDED AND WASTES LEGALLY DISPOSED OF OFF-SITE

STOCKPILE MANAGEMENT: SOIL STOCKPILES MUST BE COVERED OR STABILIZED (I.E. WITH SOIL BINDERS) IMMEDIATELY IF THEY ARE NOT SCHEDULED TO BE USED WITHIN 14 DAYS. ACTIVE SOIL STOCKPILES SHALL BE WATERED TWICE DAILY TO AVOID WIND EROSION. SURROUND ALL STOCKPILES WITH FIBER ROLLS OR SILT FENCE. STOCKPILES OF "COLD MIX" TREATED WOOD, AND BASIC CONSTRUCTION MATERIALS SHOULD BE PLACED ON AND COVERED WITH PLASTIC SHEETING OR COMPARABLE MATERIAL AND SURROUNDED BY A BERM.

> CONTRACTOR'S STAGING AREA: THE CONTRACTOR'S STAGING AREA SHALL BE SURROUNDED BY FIBER ROLLS. THE STAGING AREA WILL BE USED TO STORE DELIVERED MATERIALS, AND FOR OVERNIGHT EQUIPMENT PARKING/FUELING. STORED CONSTRUCTION MATERIALS SHALL BE MAINTAINED IN THEIR ORIGINAL CONTAINERS, AND COVERED AT ALL TIMES. PETROLEUM PRODUCTS AND HAZARDOUS MATERIALS SHALL BE STORED WITHIN SECONDARY CONTAINMENT STRUCTURES OR A STORAGE SHED. EQUIPMENT FUELING AND MAINTENANCE WILL ONLY OCCUR WITHIN THE DESIGNATED STAGING AREA. DRIP PANS OR ABSORBENT PADS MUST BE USED DURING ALL FUELING OR MAINTENANCE ACTIVITIES. AN AMPLE SUPPLY OF SPILL CLEANUP MATERIALS SHALL BE MAINTAINED IN THE STAGING AREA AT ALL TIMES.

WASTE MANAGEMENT: SOLID WASTES WILL BE LOADED DIRECTLY ONTO TRUCKS FOR OFF-SITE DISPOSAL. WHEN ON-SITE STORAGE IS NECESSARY, SOLID WASTES WILL BE STORED IN WATERTIGHT DUMPSTERS IN THE GENERAL STORAGE AREA OF THE CONTRACTOR'S YARD. DUMPSTERS AND/OR TRASH BINS SHALL BE COVERED AT THE END OF EACH WORK DAY. HAZARDOUS WASTES SHALL NOT BE STORED ONSITE. CONSTRUCTION DEBRIS AND GENERAL LITTER WILL BE COLLECTED DAILY AND WILL NOT BE ALLOWED NEAR DRAINAGE INLETS OR

GRAVEL BAG CHECK DAM: GRAVEL BAGS SHALL CONSIST OF WOVEN POLYPROPYLENE, POLYETHYLENE OR POLYAMIDE FABRIC, MIN. UNIT WEIGHT OF 40Z/SY. BAGS SHALL BE A MINIMUM OF 18" LONG X 12" WIDE X 3" THICK, FILLED WITH 1/2" - 1" CRUSHED ROCK. TIGHTLY ABUT BAGS AND CONSTRUCT CHECK DAM AT LEAST 3 BAGS WIDE X 2 BAGS HIGH. INSPECT CHECK DAM REGULARLY AND REMOVE ACCUMULATED SEDIMENT.

TREE PROTECTION: TREE PROTECTION SHALL CONSIST OF ORANGE PLASTIC MESH FENCING, AND SHALL BE INSTALLED PRIOR TO COMMENCEMENT OF EARTH-MOVING OPERATIONS (SEE DETAIL). INSTALL FENCING ALONG THE DRIP LINE OF TREES, AND INSTRUCT EMPLOYEES AND SUBCONTRACTORS TO HONOR PROTECTIVE DEVICES. TREE INJURIES SHALL BE ATTENDED TO BE A LICENSED AND CERTIFIED ARBORIST.

SILT FENCE: SILT FENCE SHALL CONSIST OF WOVEN GEOTEXTILE FABRIC WITH A MINIMUM WIDTH OF 36 INCHES. WOOD STAKES SHALL BE COMMERCIAL QUALITY LUMBER, SPACED A MAXIMUM OF 6' APART AND DRIVEN SECURELY INTO THE GROUND (SEE DETAIL). FENCING FABRIC SHALL BE KEYED INTO THE SOIL AS PER MANUFACTURER'S RECOMMENDATIONS. INSTALL SILT FENCE ALONG LEVEL CONTOURS. TURN THE ENDS OF THE SILT FENCE UPHIL TO PREVENT WATER FROM FLOWING AROUND THE FENCE. INSPECT SILT FENCE DAILY, AND MAKE REPAIRS IMMEDIATELY.

CONSTRUCTION BEST MANAGEMENT PRACTICES (BMPs)

Construction Projects Are Required to Implement the Stormwater Best Management Practices (BMPs) on this Page, as they Apply to Your Project, All Year Long.



☐ Sweep or vacuum any street

tracking immediately and

secure sediment source to

☐ Cover waste disposal

and during wet weather.

toilets, and inspect them

frequently for leaks and

☐ Clean or replace portable

MATERIALS & WASTE MANAGEMENT

Non-Hazardous Materials ☐ Berm and securely cover stockpiles of sand, dirt, or other construction materials with tarps when rain is forecast or if stockpiles are not actively being used. For best results, this should be done at the end of the work day throughout

Waste Management ☐ The California Green Building Code requires all permitted construction when feasible. residential and non-residential ☐ Use (but don't overuse) construction, demolition and reclaimed water for dust control. Hazardous Materials 65% of nonhazardous

as pesticides, paints, thinners, solvents, fuel, oil, and antifreeze) in accordance with city, county, state and federal regulations. ☐ Store hazardous materials and wastes in water tight containers, store in appropriate secondary containment, and cover them at the end of every work day or during wet weather or when rain

☐ Label all hazardous materials

and hazardous wastes (such

is forecast. ☐ Follow manufacturer's application instructions for hazardous materials and be careful not to use more than necessary. Do not apply chemicals outdoors when rain is forecast within 24 hours. ☐ Arrange for appropriate disposal of all hazardous wastes.

Construction Entrances and ☐ Establish and maintain effective perimeter controls and stabilize all construction entrances and exits to sufficiently control erosion and

and tracking off site.

sediment discharges from site



MANAGEMENT & SPILL CONTROL

Maintenance and Parking ☐ Designate an area, fitted with appropriate BMPs, for vehicle prevent further tracking. Never and equipment parking and hose down streets to clean up ☐ Perform major maintenance, repair jobs, and vehicle and

equipment washing off site. ☐ If refueling or vehicle maintenance must be done onsite, work in a bermed area away from storm drains and additions/alterations projects to over a drip pan big enough recycle or salvage a minimum to collect fluids. Recycle or

dispose of fluids as hazardous construction materials from the ☐ If vehicle or equipment cleaning must be done onsite, containers securely with tarps clean with water only in a at the end of every work day bermed area that will not allow rinse water to run into gutters, streets, storm drains, or surface

waters. ■ Do not clean vehicle or spills. Incorporate secondary equipment onsite using soaps, containment and locate them solvents, degreasers, steam away from storm drain inlets. cleaning equipment, etc. ☐ Inlet protection is the last

a manner not impeding traffic

☐ Dispose of liquid residues from paints, thinners, solvents, line of spill defense. Drains/ glues, and cleaning fluids as inlets that receive storm water hazardous waste (the Monterey Regional Waste Management must be covered or otherwise protected from receiving District offers a Household sediment/dirt/mud, other Hazardous Waste Facility that debris, or illicit discharges. accepts these items). and include gutter controls and filtration where applicable in

Spill Prevention and Control ☐ Keep spill cleanup materials (rags, absorbents, etc.)

available at the construction

site at all times. ■ Inspect vehicles and equipment frequently for and repair leaks promptly. Use drip pans to erosion control fabric or catch leaks until repairs are Clean up spills or leaks

immediately and dispose of

and/or rags).

bury them.

cleanup materials properly where construction is not (see the Monterey Regional immediately planned. Waste Management Districts **Sediment Control** guidelines for accepting hazardous waste materials). Protect storm drain inlets. gutters, ditches, and drainage ☐ Do not hose down surfaces courses with appropriate where fluids have spilled

BMPs, such as gravel bags, Use dry cleanup methods inlet filler, berms, etc. (absorbent materials, cat litter, ☐ Prevent sediment from migrating offsite by installing Sweep up spilled dry materials and maintaining sediment immediately. Do not try to controls, such as fiber rolls, silt wash them away with water, or

☐ Keep excavated soil on the site Clean up spills on dirt areas where it will not collect into by digging up and properly disposing of contaminated soi (see the Monterey Regional ☐ Transfer excavated materials to Waste Management District's dump trucks on the site, not in Contaminated Soil Acceptance Criteria). ☐ If any of the following

☐ Report significant spills immediately. You are required by law to report all significant releases of hazardous materials. including oil. To report a spill:



EARTHWORK & PAVING/ASPHALT CONTAMINATED SOILS

Erosion Control ☐ Avoid paving and seal coating ☐ Store concrete, grout and mortar in wet weather, or when rain is ☐ Schedule grading and forecast before fresh pavement excavation work for dry will have time to cure. weather only. □ Cover storm drain inlets and ☐ Stabilize all denuded areas. manholes when applying seal install and maintain temporary coat, tack coat, slurry seal, fog erosion controls (such as

□ Collect and recycle or bonded fiber matrix) until vegetation is established. appropriately dispose of excess abrasive gravel or sand. Do Seed or plant vegetation for NOT sweep or wash it into erosion control on slopes of ■ Do not use water to wash

> down fresh asphalt or concrete pavement. Sawcutting & Asphalt/Concrete ☐ Completely cover or barricade

WORK

cutting. Use filter fabric, catch basin inlet filters, or gravel bags to keep slurry out of the storm drain system. □ Protect storm drain inlets. gutters, ditches, and drainage

storm drain inlets when saw

courses with appropriate BMPs, such as gravel bags, inlet filters, berms, etc. ☐ Shovel, abosorb, or vacuum saw-cut slurry and dispose of all waste as soon as you are finished in one location or

at the end of each work day (whichever is sooner!). ☐ If sawcut slurry enters a catch basin, clean it up immediately.



CONCRETE GROUT&

MORTAR APPLICATION under cover, on pallets and away from drainage areas. These materials must never reach a storm drain

■ Wash out concrete equipment/ trucks offsite or in a contained area, so there is no discharge into the underlying soil or onto surrounding areas. Let concrete harden and dispose of as garbage.

☐ Collect the wash water from washing exposed aggregate concrete and remove it for appropriate disposal offsite

MATERIALS

being used.

weather.

rain event or during wet

Paint Removal ☐ Chemical paint stripping residue and chips and dust from marine paints or paints containing lead or tributyltin must be disposed of as LANDSCAPE

hazardous waste. ☐ Paint chips and dust from ☐ Contain stockpiled landscaping materials by storing them under tarps when they are not actively

non-hazardous dry stripping and sand blasting may be swept

REMOVAL

☐ Never clean brushes or rinse

☐ For water-based paints, paint

out brushes to the extent

possible. Rinse to the sanitary

wastewater treatment authority.

Never pour paint down a drain.

☐ For oil-based paints, paint out

solvent in a proper container

Filter and reuse thinners and

unusable thinner/solvents as

hazardous waste.

solvents. Dispose of residue and

and clean with thinner or

brushes to the extent possible

sewer once you have gained

permission from the local

paint containers into a street,

gutter, storm drain, or surface

Painting cleanup



PAINTING & PAINT DEWATERING

Effectively manage all run-on. all runoff within the site, and all runoff that discharges from ☐ Divert run-on water from offsite away from all disturbed areas or

otherwise ensure protection of its water quality for compliance. ☐ When dewatering, notify and obtain approval from the local municipality before discharging water to a street gutter or storm drain. Filtration or diversion

through a basin, tank, or sediment trap, and/or disposal in sanitary sewer may be required. In areas of known contamination, testing is required prior to reuse or discharge of groundwater. Consult with the Engineer and

municipal staff to determine whether testing is required and how to interpret results Contaminated groundwater must be treated or hauled offsite for proper disposal.

|08/16/24| AMS | RELEASED TO CLIENT No. DATE BY

SCALE: AS SHOWN DATE: AUGUST 2024 OB NO. 2816-01

 \vdash

SHEETS

STORM DRAIN POLLUTERS MAY BE LIABLE FOR FINES OF UP TO \$10,000 PER DAY!

conditions are observed.

Environmental Health

test for contamination and

contact the Monterey County

Department, Regional Water

Quality Control Board, and

local municipal inspector:

Unusual soil conditions.

discoloration, or odor


Abandoned wells


Abandoned underground tank

up or collected in plastic drop cloths and disposed of as trash ☐ Stack erodible landscape material on pallets. Cover or store these materials when they are not actively being used or ☐ Discontinue application of any erodible landscape material within 2 days before a forecast

Adapted with permission from the San Mateo Countywide Water Pollution Prevention Program

· Buried barrels, debris, or trash.





FENCING (ESA) DETAIL

EARTHWORK QUANTITIES PER CIVIL ENGINEERING PLANS BY LANDSET ENGINEERS, INC.:

20 CY FILL

DEMOLISH EXISTING HARDSCAPE AND OFFHAUL DEBRIS: EXISTING DRIVEWAY TO BE USED FOR EQUIPMENT STAGING AND TEMPORARY STOCKPILE AREA.

PERFORM MINOR GRADING, CONSTRUCT STRUCTURE ADDITIONS, AND INSTALL UNDERGROUND UTILITIES: EXISTING DRIVEWAY AREA TO BE USED FOR MATERIAL AND EQUIPMENT STAGING.

INSTALL NEW PAVERS DRIVEWAY AND LANDSCAPING.

SEE ARCHITECTURAL AND CIVIL PLANS FOR EROSION CONTROL AND DEMOLITION NOTES.

CONSTRUCTION EQUIPMENT AND MATERIALS SHALL NOT BE STAGED ON MISSION STREET AT ANY TIME DURING CONSTRUCTION. MATERIAL DELIVERIES SHALL BE SCHEDULED SUCH THAT THEY ARE USED PROMPTLY, AND MATERIAL STORAGE IS MINIMIZED. ALL CONSTRUCTION EQUIPMENT AND MATERIALS SHALL BE STORED IN A DESIGNATED AREA ON THE SUBJECT PROPERTY.

THE HAUL ROUTE TO THE SITE IS FROM HIGHWAY 1 TO CARPENTER STREET TO SERRA AVENUE TO ALTA AVENUE TO MISSION STREET. (HAUL TRUCKS EXIT IN THE SAME FASHION.) VEHICLES SHALL NOT BE LEFT UNATTENDED WHILE IN QUEUE (IF NECESSARY) ON MISSION STREET. CONTRACTOR TO ENSURE THAT HEIGHT RESTRICTIONS WITHIN THE DRIVEWAY AREA SHALL BE ADDRESSED BEFORE CONSTRUCTION VEHICLES ENTER THE SITE. SEE DETAILS B AND C, TRUCK ROUTING PLANS.

IN THE EVENT THAT MATERIAL DELIVERIES CAUSE ANY STREETS ALONG THE HAUL ROUTE TO BE PARTIALLY BLOCKED BY DELIVERY TRUCKS OR LOADING/UNLOADING OPERATIONS, A FLAGMAN SHALL BE PRESENT TO DIRECT TRAFFIC AROUND THE LANE OBSTRUCTION. THE FLAGMAN SHALL BE PRESENT AT ALL TIMES DURING WHICH DELIVERY/ CONSTRUCTION OPERATIONS MAY IMPACT TRAFFIC ON THE HAUL ROUTE AND SURROUNDING STREETS.

LIMITED EMPLOYEE PARKING ON-SITE. EMPLOYEES SHALL USE PUBLIC PARKING LOTS AND CARPOOL TO JOBSITE IF POSSIBLE. ON-SITE PARKING SHALL BE IN LEGAL SPACES ALONG MISSION STREET, OBEYING ALL PARKING LAWS. PARKING IS PROHIBITED IN ALL NATURAL AREAS WHICH ARE NOT CURRENTLY PAVED OR GRAVEL.

<u>LIMITS OF CONSTRUCTION:</u> ALL CONSTRUCTION SHALL TAKE PLACE WITHIN THE BORDER AS SHOWN. EXISTING CYPRESS, PINE, AND OAK TREES LOCATED WITHIN THE LIMITS SHOWN SHALL BE SURROUNDED BY ORANGE PROTECTIVE FENCING (SEE DETAIL).

TRUCK TRIP GENERATION CHART:


CATEGORY	NO. OF TRUCK TRIPS	TOTAL DAYS
DEMOLITION/CLKEARING	4	4
GRADING & SOIL REMOVAL (EXPORT)	8	2
ENGINEERING MATERIALS (IMPORT)	3	4
TOTALS	15	10

TRUCK TRIP GENERATION NOTES:

- 1. TRUCK TRIPS FOR THE GRADING/SOIL REMOVAL IS BASED UPON 20 CUBIC YARDS PER TRUCKLOAD WITH AN AVERAGE OF 5 TRUCK LOADS PER DAY. 2. THERE ARE 145 C.Y. OF SURPLUS SOIL MATERIAL THAT WILL BE EXPORTED OFF THE SITE.
- 3. GRADING OPERATIONS SHALL TAKE APPROXIMATELY 10 WORKING DAYS TO
- 4. THE AMOUNT OF GRADING PER DAY WILL VARY, THE AVERAGE BETWEEN 80 & 120 CUBIC YARDS.
- NUMBER OF EMPLOYEES/DAY: 4-10

HOURS OF OPERATION/DAY: 8

PROJECT SCHEDULING: PROJECTED START DATE 9 SEPTEMBER 2024, 7 WORKING DAYS TO COMPLETE GRADING, MONDAY THRU FRIDAY, 8:00 A.M. - 4:30 P.M. TOTAL PROJECT DURATION IS APPROXIMATELY 12 MONTHS.



08/16/24 AMS RELEASED TO CLIENT

No. DATE BY

OF 3 SHEETS

MISSION SISTERS - LOT 6 HAPUNA

MISSION STREET 4 NE OF FIRST AVE CARMEL-BY-THE-SEA, CA 93923 APN # 010-112-012

FRONT ELEVATION



ABBREVIATIONS

AMERICANS WITH DISABILITIES ACT ADJ ADJACENT CBC CL CLR CALIFORNIA BUILDING CODE **CENTER LINE** CONC CONCRETE DRAIN INLET **EXISTING EXPANSION JOINT EQUAL** FINISH FLOOR ELEVATION FINISH GRADE FINISH SURFACE HIGH POINT INVERT LIMIT OF WORK LOW POINT MAXIMUM MANHOLE MAINLINE ON CENTER PULL BOX QUICK COUPLER VALVE RELATIVE COMPACTION RIM ELEVATION STORM DRAIN TOP OF SURFACE

TREE PROTECTION ZONE


UNLESS NOTED OTHERWISE

UNLESS OTHERWISE NOTED

TOP OF WALL
TYPICAL

VERIFY IN FIELD

VICINITY MAP



PROJECT MAP




PROJECT DESCRIPTION

THE LANDSCAPE FOR THE PROPOSED RESIDENCE WILL REVIVE THE FRACTURED OAK WOODLAND THAT IS ALREADY PRESENT ON THE SITE. BY ADDING LAYERS OF (MOSTLY) NATIVE OAK WOODLAND PLANTS IN THEIR NATURAL PATTERNS OF GROWTH, THE WOODLAND WILL COME TO LIFE AGAIN AND BRING BEAUTY TO BOTH THE NEW OWNERS AND THE NEIGHBORHOOD ALIKE. ALL PAVING AND HARDSCAPE MATERIALS HAVE BEEN SELECTED TO MAINTAIN THIS NATURAL AESTHETIC.

INDEX OF DRAWINGS

SHEET NUMBER	SHEET TITLE
L0.00	LOT 6 HAPUNA COVER SEET
L1.00	OVERALL SITE PLAN
L1.01	LOT 6 HAPUNA SITE PLAN
L2.00	LOT 6 HAPUNA PLANTING PLAN
L2.01	LOT 6 HAPUNA PLANTING LEGEND AND NOTES
L3.00	LOT 6 HAPUNA LIGHTING PLAN





ARCHITECT

DYAR ARCHITECTURE

PO BOX 4709

CARMEL, CA 93921

831.250.7378

e a m

LYNNE HERMLE + CRAIG J. COLLINS

o w n e r

MISSION SISTERS

MISSION STREET 2, 3, & 4 NE OF FIRST AVE CARMEL-BY-THE-SEA, CA 93923 APN # 010-112-012, 010-112-013, 010-112-007

project

1	TRACK 2 DESIGN STUDY RESUBMITTAL	09.04.20
1	PLANNING APPLICATION	07.01.20

no. description

date:

09.04.2024


LOT 6 HAPUNA COVER SEET

sheet title

L0.00

sheet no.

9/9/2024 12:37 PN



t e a m

s e a l

ARCHITECT

DYAR ARCHITECTURE PO BOX 4709

CARMEL, CA 93921

831.250.7378

LYNNE HERMLE CRAIG J. COLLINS

owner

MISSION SISTERS

MISSION STREET 2, 3, & 4 NE OF FIRST AVE CARMEL-BY-THE-SEA, CA 93923 APN # 010-112-012, 010-112-013, 010-112-007

project

TRACK 2 DESIGN STUDY RESUBMITTAL 1 PLANNING APPLICATION

no. description

09.04.2024

OVERALL SITE PLAN

sheet title

L1.00

sheet no.

LEGEND

"I, MARIE GOULET, CERTIFY THAT THIS LANDSCAPING AND IRRIGATION PLAN COMPLIES WITH ALL MONTEREY COUNTY LANDSCAPING REQUIREMENTS INCLUDING USE OF NATIVE DROUGHT TOLERANT, NON-INVASIVE SPECIES, LIMITED TURF AND LOW FLOW, WATER CONSERVING IRRIGATION FIXTURES."

ASPHALT PAVING DECOMPOSED GRANITE PAVING DECK MULCH PATH

PLANTING AREA DRIVEWAY / ENTRY STONES: 14" x 48"

STONE WALL CORTEN STEEL WALL BOULDER EXISTING TREE

PROPOSED TREE -PROPOSED FENCE ----- HEADERBOARD

EXISTING CONTOURS PROPOSED CONTOURS ----- PROPERTY LINE

+FS 53.5 PROPOSED SPOT ELEVATIONS ---> FLOWLINE

NUMBERED NOTES

1 DECK

2 SINGLE PEDESTRIAN GATE

(3) MULCH PATH

(4) MULCH DINING AREA WITH FIREPLACE (5) BBQ AREA

(6) ENTRY

(7) TRASH AREA

(8) SCULPTURE / FOUNTAIN / FOCAL POINT

9 DRIVEWAY

(10) GUEST PARKING (11) ENTRY WALKWAY

(12) RAINGARDEN / SWALE


(13) LOW STONE WALLS 14 STONE FIREPLACE - 4' TALL

(E) WALL TO REMAIN

DESCRIPTION OF WORK

THE FULLY REDESIGNED LANDSCAPE SURROUNDING THE NEW RESIDENCE IS DESIGNED TO BLEND THE ARCHITECTURE INTO THE EXISTING AND ENHANCED NATIVE OAK/ PINE WOODLAND WHILE CREATING OUTDOOR ROOMS CONNECTED TO THE ARCHITECTURE FOR DINING AND RELAXATION. DENSE AND LAYERED NATIVE PLANTINGS PROVIDE YEAR ROUND INTEREST AND PROVIDE PRIVACY FROM NEIGHBORS. STORMWATER IS DIRECTED TO PLANTED BIOSWALES AND RAIN GARDENS.

PRECEDENT IMAGES















OUTDOOR PATIO




PERSPECTIVE RENDERING









ARCHITECT DYAR ARCHITECTURE PO BOX 4709 CARMEL, CA 93921 831.250.7378

team

LYNNE HERMLE CRAIG J. COLLINS

owner

MISSION SISTERS

MISSION STREET 2, 3, & 4 NE OF FIRST AVE CARMEL-BY-THE-SEA, CA 93923 APN # 010-112-012, 010-112-013, 010-112-007

project

1	TRACK 2 DESIGN STUDY RESUBMITTAL	09.04.2024
1	PLANNING APPLICATION	07.01.2024

no. description


09.04.2024

LOT 6 HAPUNA SITE PLAN

sheet title

L1.01

sheet no.







ARCHITECT
DYAR ARCHITECTURE
PO BOX 4709
CARMEL, CA 93921
831.250.7378

t e a m

LYNNE HERMLE + CRAIG J. COLLINS

o w n e r

MISSION SISTERS

MISSION STREET 2, 3, & 4 NE OF FIRST AVE CARMEL-BY-THE-SEA, CA 93923 APN # 010-112-012, 010-112-013, 010-112-007

project

1	TRACK 2 DESIGN STUDY RESUBMITTAL	09.04.20
1	PLANNING APPLICATION	07.01.20

no. description

dat

09.04.2024

LOT 6 HAPUNA PLANTING PLAN

sheet title

L2.00

sheet no.

9/9/2024 12:38 PM

MATRIX PLANTS:











PRUNELLA VULGARIS

HAPUNA ACCENT PLANTS:





ARCTOSTAPHYLOS HOOKERI 'WAYSIDE'



IRIS DOUGLASIANA 'CANYON SNOW'

HEUCHERA MAXIMA





RIBES SANGUINEUM 'WHITE ICICLE'

HAPUNA SCREENING PLANTS:



HAPUNA TREES:

ARCTOSTAPHYLOS 'DR. HURD'









LOT 6 HAPUNA

TREE LEGEND

1	BOTANICALNAME	COMMONNAME	SIZE	SPACING	Count
	ARCTOSTAPHYLOS MANZANITA 'DR. HURD'	DR. HURD MANZANITA	24" BOX	AS SHOWN	1

SHRUB AND GROUND COVER LEGEND

KEY	BOTANICAL NAME	COMMON NAME	SIZE	SPACING	QUANTITY
AC	ACANTHUS MOLLIS	BEAR'S BREECHES	5 GAL	2' OC	9
Α	ACHILLEA MILLEFOLIUM	COMMON YARROW	1 GAL	1'-6" OC	3
AQ	AQUILEGIA CAERULEA	COLORADO COLUMBINE	1 GAL	2' OC	69
AD	ARCTOSTAPHYLOS DENSIFLORA 'HOWARD MCMINN'	HOWARD MCMINN MANZANITA	15 GAL	4' OC	3
AH	ARCTOSTAPHYLOS HOOKERI 'WAYSIDE'	MONTEREY MANZANITA	15 GAL	4' OC	7
+	ARMERIA MARITIMA SSP CALIFORNICA	SEA THRIFT	1 GAL	1' OC	25
AR	ARTEMISIA 'DAVID'S CHOICE'	SAND HILL SAGE	5 GAL	2' OC	2
В	BLECHNUM SPICANT	DEER FERN	1 GAL	1' OC	47
CN	CALAMAGROSTIS NUTKAENSIS	PACIFIC REED GRASS	5 GAL	3' OC	6
CP	CAREX PANSA	DUNE SEDGE	1 GAL	1' OC	734
CR	CEANOTHUS 'RAY HARTMAN'	CALIFORNIA LILAC	15 GAL	4' OC	24
CD	CLINOPODIUM DOUGLASII	YERBA BUENA	1 GAL	1'-0"	77
D	DYMONDIA MARGARETAE	SILVER CARPET	PLUGS	1' OC	123
FC	FESTUCA CALIFORNICA	CALIFORNIA FESCUE	1 GAL	1'-6" OC	5
НМ	HEUCHERA MAXIMA	ISLAND ALUM ROOT	1 GAL	2' OC	21
IC	IRIS DOUGLASIANA 'CANYON SNOW'	CANYON SNOW DOUGLAS IRIS	1 GAL	1'-6" OC	71
PM	POLYSTICHUM MUNITUM	SWORD FERN	5 GAL	2' OC	13
Р	PRUNELLA VULGARIS	COMMON SELFHEAL	1 GAL	8" OC	121
RA	RIBES AUREUM	GOLDEN CURRANT	5 GAL	3' OC	3
RW	RIBES 'WHITE ICICLE'	WHITE WINTER CURRANT	15 GAL	6' OC	1
SD	SALVIA 'DARA'S CHOICE'	CREEPING SAGE	5 GAL	2'-6" OC	16
SS	SALVIA SPATHACEA	HUMMINGBIRD SAGE	5 GAL	2' OC	2
Т	THYMUS PSEUDOLANUGINOSUS	WOOLLY THYME	PLUGS	6" OC	326
WF	WOODWARDIA FIMBRIATA	GIANT CHAIN FERN	PLUGS	4' OC	3

VINE LEGEND

KEY	BOTANICALNAME	COMMONNAME	SIZE	SPACING	Count
V	VITIS CALIFORNICA 'ROGER'S RED'	CALIFORNIA WILD GRAPE	1 GAL	AS SHOWN	2

PLANTING NOTES:


PLANTING DESIGN AND IRRIGATION DESCRIPTION:
THE INTENT OF THIS DESIGN IS TO BLEND THE ARCHITECTURE INTO THE SURROUNDING LANDSCAPE WITH NATIVE SPECIES
APPROPRIATE FOR THE AREA. THE NEW LANDSCAPE FOR THE RESIDENCE IS IN KEEPING WITH THE OAK WOODLAND ECOTYPE
IN CARMEL. PLANTS SHALL BE MINIMALLY IRRIGATED WITH A DRIP SYSTEM ON THE PROPERTY, CONTROLLED WITH AN ET
CONTROLLER AND RAIN SENSOR. PLANTING DESIGN ON ADJACENT LOTS SHOWN FOR REFERENCE ONLY.

SOIL AMENDMENT

1. ALL SHRUB PLANTING AREAS TO RECEIVE 3" DEEP MULCH, VERIFY SPEC WITH LANDSCAPE ARCHITECT.

2. AMEND SOIL BASED ON SITE SPECIFIC SOIL TESTING RECOMMENDATIONS, CONTRACTOR TO SEND SOIL SAMPLES OUT FOR TESTING AND PROVIDE RESULTS TO OWNER AND LANDSCAPE ARCHITECT.

WILD LAND W O R K S H O P LANDSCAPE ARCHITECTURE



ARCHITECT DYAR ARCHITECTURE PO BOX 4709 CARMEL, CA 93921 831.250.7378

t e a m

LYNNE HERMLE CRAIG J. COLLINS

owner

MISSION SISTERS

MISSION STREET 2, 3, & 4 NE OF FIRST AVE CARMEL-BY-THE-SEA, CA 93923 APN # 010-112-012, 010-112-013, 010-112-007

project

1	TRACK 2 DESIGN STUDY RESUBMITTAL	09.04.202
1	PLANNING APPLICATION	07.01.202

no. description

09.04.2024

LOT 6 HAPUNA PLANTING LEGEND AND NOTES

sheet title


L2.01

sheet no.



I, MARIE GOULET, CERTIFY THAT THIS LANDSCAPING AND IRRIGATION PLAN COMPLIES WITH ALL MONTEREY COUNTY LANDSCAPING REQUIREMENTS INCLUDING USE OF NATIVE DROUGHT TOLERANT, NON-INVASIVE SPECIES, LIMITED TURF AND LOW FLOW, WATER CONSERVING IRRIGATION FIXTURES.

WILD LAND
WORKSHO
PLANDSCAPE ARCHITECTURE



ARCHITECT
DYAR ARCHITECTURE
PO BOX 4709
CARMEL, CA 93921
831.250.7378

t e a m

LYNNE HERMLE + CRAIG J. COLLINS

o w n e r

MISSION SISTERS

MISSION STREET 2, 3, & 4 NE OF FIRST AVE CARMEL-BY-THE-SEA, CA 93923 APN # 010-112-012, 010-112-013, 010-112-007

project

 1
 TRACK 2 DESIGN STUDY RESUBMITTAL
 09.04.2024

 1
 PLANNING APPLICATION
 07.01.2024

no. description

date:

1/8" = 1' - 0"

T 0 1 1 4 D1 1 1 4 1 1 0 1 T1 1 0

09.04.2024

LOT 6 HAPUNA LIGHTING PLAN

sheet title

L3.00 sheet no.

o d t