

# Cylinder LED Downlight Wall Sconce



## Description:

11250 LED Outdoor Wall Sconce features a downlight only cylinder used to highlight architectural surfaces. Made of cast aluminum with powder coat Textured Architectural Bronze or Textured Black finish. Includes ten 120 volt LEDs totaling 10 watts with Pure White 3000K, 90CRI color temperature, 374 lumens. 40,000 hour average lamp life. 4.5 inch width x 7 inch height x 6.5 inch depth. UL listed. Suitable for wet locations. Dark Sky Compliant. Title 24 Compliant.

**RECEIVED**

**JAN 22 2019**

City of Carmel-by-the-Sea  
Planning & Building Dept.

Shown in: Textured Architectural Bronze

**List Price:** \$162.50  
**Our Price:** \$130.00

**Shade Color:** N/A  
**Body Finish:** Textured Architectural Bronze  
**Lamp:** 1 x LED/10W/120V LED  
**Wattage:** 10W  
**Dimmer:** Not Dimmable  
**Dimensions:** 5"W x 7"H x 6.5"D

## Technical Information

**Lamp Color:** 3000 K  
**Color Rendering:** 85 CRI

Product Number: <b>KHR349587</b>					
Company:			Fixture Type:		Date: Jan 22, 2019
Project:			Approved By:		

Fax: (773) 883-6131

Phone: 866-954-4489

Address: 1718 W. Fullerton Ave. Chicago IL 60614

www.Lightology.com

# WAC LIGHTING

Responsive Home Lighting®

Home » Step and Wall Lights

Explore Our Products

Applications

Be Inspired

Connect with Us

Resources

Where to buy

Login

Search



Click image to zoom  
Upload your own photo  
Where to buy?



## WL-LED140

120V/277V Rectangular Step and Wall Lights

- Power: 3.5W(120V), 3W(277V)
- Input: 120V, 277V
- Lumen: Up to 3lm
- CRI: 90
- Dimming: 100% - 10% ELV (120V only)
- Rated Life: 50,000 hours
- Geometric design with downward illumination
- Die Cast Aluminum construction with abrasion resistant finish
- Title 24 Compliant (120V only)
- IP66 rated self contained fixture with various face plates
- Fits into a switch box or a 2" x 4" Junction box with minor dimensions of 3" L x 2" W x 2.5" D
- Magnetized design for easy installation and maintenance
- ETL & cETL listed

### Finishes

BB

BK

WT

